

Beta ELECTRONICS
 Digital temperature, humidity and pressure controllers

temperature | pressure | humidity | milk preservation | accessories

Home page | Site Map

claiton | Search

- Company
- Our mission
- R & D
- Sales Department
- Where we are
- News
- Products
 - Temperature Control
 - Pressure Control
 - Humidity Control
 - Milk Preservation
 - Accessories
 - PTC Probes
 - PT100 thermal resistors
 - Thermocouples
 - Humidity transducers
 - Pressure transducers
 - Transformers
 - Network filters
 - Power relays
 - Connection cables
 - Metal pockets for probes
 - Batteries
 - Other
 - Customised
- Thermoregulation for civil
- Support
- Site Map
- Search
- Join us
- Contact us



PTC Probes

S6.P; S6.R; S6.S; PTC300-S; PTC300-V; PTC-GLOBO



S6.P: Resin treated probe, 7 x 25 mm plastics sensor housing, PVC cable 2 m long Range -20 χ +105°C

No available description

S6.R: Resin treated probe, 6 x 30 mm stainless steel sensor housing, PVC cable 2 m long Range -20 χ +105°C

S6.S: Resin treated probe, 6 x 30 mm stainless steel sensor housing, silicon cable 2 m long Range -50 χ +140°C

PTC300-S: CH treated probe, 6 x 100 mm stainless steel sensor housing, silicon cable 2 m long Range -50 χ +180°C

PTC300-V: CH treated probe, 6 x 100 mm stainless steel sensor housing, vetrotex cable 2 m long Range -40 χ +270°C

PTC-GLOBO: Wall mounting PTC probe with "globe" sensor Range -10 χ +50°C

