



CARATTERISTICHE PRINCIPALI

Sonde con sensore sensibile alla luce

SCPLUX/A	Sonda con sensore sensibile alla luce, puntale 8x30 in materiale trasparente, 2mt cavo in PVC temperatura d'impiego -20T60°C, IP67
SCPLUX/B	Sonda con sensore sensibile alla luce, puntale 8x30 in materiale trasparente, 3mt cavo in PVC temperatura d'impiego -20T60°C, IP67
SCPLUX/C	Sonda con sensore sensibile alla luce, puntale 8x30 in materiale trasparente, 6mt cavo in PVC temperatura d'impiego -20T60°C, IP67

CARATTERISTICHE TECNICHE

Sensore LUX 100KΩ @0.1 Lux - 700Ω @1000 Lux



MAIN FEATURES

Light probes

SCPLUX/A	Probe with photo conductive sensor, 8x30 plastic ferrule, 2mt cable in PVC employment temperature -20T60°C, IP67
SCPLUX/B	Probe with photo conductive sensor, 8x30 plastic ferrule, 3mt cable in PVC employment temperature -20T60°C, IP67
SCPLUX/C	Probe with photo conductive sensor, 8x30 plastic ferrule, 6mt cable in PVC employment temperature -20T60°C, IP67

TECHNICAL FEATURES

LUX sensor: 100KΩ @0.1 Lux - 700Ω @1000 Lux