

Rubinetto portamanometro a membrana per gas

Corpo: ottone nichelato

Caratteristiche: pulsante a rilascio lento per la lettura della pressione

Pressione: max PN 4bar

Automatic push bottom valve for gases

Body: nichel plated brass

Features: push bottom with slow release for pressure reading

Pressure: max PN4 bar



ACRG

Codice/Part. No	Denominazione/Description	Esecuzione standard/Supplied standard	Conf./Pack.
ACRG00001	ACRG 1/4 x 1/4		10
ACRG00002	ACRG 3/8 x 3/8		10
ACRG00003	ACRG 1/2 x 1/2		10

Ammortizzatore in rame

Serpentina in rame PN 30 bar

Attacco: maschio-femmina

Vibration dampener

Copper tube brass connection

Connection: male-female NP 30 bar



ACSR

Codice/Part. No	Denominazione/Description	Esecuzione standard/Supplied standard	Conf./Pack.
ACSR00001	ACSR 1/4F x 1/4M		10
ACSR00002	ACSR 3/8F x 1/4M		10
ACSR00003	ACSR 1/2F x 1/2M		10

Rubinetto portamanometro flangiato

Corpo: in ottone a tre vie

PN 25 bar - per esercizio 15 bar temperatura max 90°C

Flangia: DN 40 per manometro di controllo

Attacco: maschio-femmina

Manual shut off valve with test flange

Body: brass - 2 ways + test flange

NP 25 bar - Working pressure max. 15 bar temperature 90°C

Flange: DN 40 for test gauge

Connection: male-female



ACRF

Codice/Part. No	Denominazione/Description	Esecuzione standard/Supplied standard	Conf./Pack.
ACRF00001	ACRF 1/4F x 1/4M		10
ACRF00002	ACRF 3/8F x 3/8M		10
ACRF00003	ACRF 1/2F x 1/2M		10

Rubinetto portamanometro

Corpo: in ottone a due vie

PN 25 bar - per esercizio 15 bar temperatura max 90°C

Attacco: maschio-femmina

Manual shut off valve

Body: brass - 2 ways

NP 25 bar - Working pressure max. 15 bar temperature 90°C

Connection: male-female



ACRP

Codice/Part. No	Denominazione/Description	Esecuzione standard/Supplied standard	Conf./Pack.
ACRP00001	ACRP 1/4F x 1/4M		10
ACRP00002	ACRP 3/8F x 3/8M		10
ACRP00003	ACRP 1/2F x 1/2M		10