

Manometro DN 63/100 cassa acciaio INOX AISI 304

Cassa: acciaio INOX AISI 304

Trasparente: policarbonato

Anello: acciaio INOX AISI 304

Elemento Manometrico: molla Bourdon in lega di rame

Attacco: radiale in ottone

Saldature: in lega di stagno per temperature da -20 +90 °C

Movimento amplificatore di precisione: in ottone per orologeria

Precisione: CL. 1,6

Protezione: IP 65

MLR 63/100: pressure gauge ND 63/100 S.S. case AISI 304

Case: S.S. AISI 304

Window: polycarbonate

Ring: S.S. AISI 304

Sensing element: copper alloy Bourdon tube

Connection: brass – bottom connection

Welding: tin alloy for working temperature ranging from -20 +90 °C

Amplifying movement: brass for precision clockwork

Accuracy: Cl. 1,6

Protection: IP 65



MLR 63/100

63

Codice/Part. No Denominazione/Description Esecuzione standard/Supplied standard Conf./Pack.

MLR63V01EJ	MLR-63	INOX -1.0 bar/inHg	G1/4B		50
MLR63B01DJ	MLR-63	INOX 0.1 bar/psi	G1/4B		50
MLR63B03DJ	MLR-63	INOX 0.1,6 bar/psi	G1/4B		50
MLR63B04DJ	MLR-63	INOX 0.2,5 bar/psi	G1/4B		50
MLR63004DJ	MLR-63	INOX 0.4 bar/psi	G1/4B		50
MLR63006DJ	MLR-63	INOX 0.6 bar/psi	G1/4B		50
MLR63010DJ	MLR-63	INOX 0.10 bar/psi	G1/4B		50
MLR63012DJ	MLR-63	INOX 0.12 bar/psi	G1/4B		50
MLR63016DJ	MLR-63	INOX 0.16 bar/psi	G1/4B		50
MLR63025DJ	MLR-63	INOX 0.25 bar/psi	G1/4B		50
MLR63040DJ	MLR-63	INOX 0.40 bar/psi	G1/4B		50
MLR63060DJ	MLR-63	INOX 0.60 bar/psi	G1/4B		50
MLR63100DJ	MLR-63	INOX 0.100 bar/psi	G1/4B		50
MLR63160DJ	MLR-63	INOX 0.160 bar/psi	G1/4B		50
MLR63250DJ	MLR-63	INOX 0.250 bar/psi	G1/4B		50
MLR63315DJ	MLR-63	INOX 0.315 bar/psi	G1/4B		50
MLR63400DJ	MLR-63	INOX 0.400 bar/psi	G1/4B		50
MLR63600DJ	MLR-63	INOX 0.600 bar/psi	G1/4B		50
MLR61000DJ	MLR-63	INOX 0.1000 bar/psi	G1/4B		50

100

MLR10V01EL	MLR-100	INOX -1.0 bar/inHg	G1/2B		50
MLR10B01DL	MLR-100	INOX 0.1 bar/psi	G1/2B		50
MLR10B03DL	MLR-100	INOX 0.1,6 bar/psi	G1/2B		50
MLR10B04DL	MLR-100	INOX 0.2,5 bar/psi	G1/2B		50
MLR10004DL	MLR-100	INOX 0.4 bar/psi	G1/2B		50
MLR10006DL	MLR-100	INOX 0.6 bar/psi	G1/2B		50
MLR10010DL	MLR-100	INOX 0.10 bar/psi	G1/2B		50
MLR10012DL	MLR-100	INOX 0.12 bar/psi	G1/2B		50
MLR10016DL	MLR-100	INOX 0.16 bar/psi	G1/2B		50
MLR10025DL	MLR-100	INOX 0.25 bar/psi	G1/2B		50
MLR10040DL	MLR-100	INOX 0.40 bar/psi	G1/2B		50
MLR10060DL	MLR-100	INOX 0.60 bar/psi	G1/2B		50
MLR10100DL	MLR-100	INOX 0.100 bar/psi	G1/2B		50
MLR10160DL	MLR-100	INOX 0.160 bar/psi	G1/2B		50
MLR10250DL	MLR-100	INOX 0.250 bar/psi	G1/2B		50
MLR10315DL	MLR-100	INOX 0.315 bar/psi	G1/2B		50
MLR10400DL	MLR-100	INOX 0.400 bar/psi	G1/2B		50
MLR10600DL	MLR-100	INOX 0.600 bar/psi	G1/2B		50
MLR11000DL	MLR-100	INOX 0.1000 bar/psi	G1/2B		50

Su richiesta esecuzioni diverse e personalizzate
On request only we are available for special and personalized versions

SITEM SRL - Via San Carlo, 22 - 20053 Muggiò (Mi)

Tel. (+39) 039.27.85.390 - Fax (+39) 039.27.86.699 - E-mail: info@sitemitalia.it - web-site: www.sitemitalia.it