

Termomanometro DN 80 posteriore
Cassa: ABS nero

Trasparente: kostil con indice rosso

Elemento Manometrico: molla Bourdon in lega di rame

Elemento Termometrico: molla a spirale bimetallica

Attacco: posteriore centrale in ottone 1/4G

Saldature: in lega di stagno per temperature da -20 +90 °C

Movimento amplificatore di precisione: in ottone per orologeria

Valvola di ritegno: in ottone 1/4F x 1/2M

Precisione: Cl. 1,6

Protezione: IP 31

Combined temperature and pressure gauge ø 80 mm centre back entry
Case: ABS black

Window: kostil with red pointer

Pressure element: copper alloy Bourdon tube

Temperature element: bimetal spiral spring

Welding: tin alloy for working temperature ranging from -20 +90 °C

Connection: brass - thread 1/4G

Retaining valve: brass - thread 1/4F x 1/2M supplied together

Amplifying movement: brass for precision clockwork

Accuracy: Cl. 1,6

Protection: IP 31

TIAP/TIAF - 80

Codice/Part. No	Denominazione/Description	Esecuzione standard/Supplied standard	Conf./Pack.
TI80003PA	TIAP-80 0-2,5 bar 0/120°C VR1/2		50
TI80004PA	TIAP-80 0-4 bar 0/120°C VR1/2		50
TI80006PA	TIAP-80 0-6 bar 0/120°C VR1/2		50
TI80003FA	TIAF-80 0-2,5 bar 0/120°C VR1/2+AC	AC=Anello cromato/Chromed ring	50
TI80004FA	TIAF-80 0-4 bar 0/120°C VR1/2+AC	AC=Anello cromato/Chromed ring	50
TI80006FA	TIAF-80 0-6 bar 0/120°C VR1/2+AC	AC=Anello cromato/Chromed ring	50

Termomanometro DN 80 radiale
Cassa: ABS nero

Trasparente: kostil con indice rosso

Elemento Manometrico: molla Bourdon in lega di rame

Elemento Termometrico: molla a spirale bimetallica

Attacco: posteriore centrale in ottone 1/4G

Saldature: in lega di stagno per temperature da -20 +90 °C

Movimento amplificatore di precisione: in ottone per orologeria

Valvola di ritegno: in ottone 1/4F x 1/2M

Precisione: Cl. 1,6

Protezione: IP 31

Combined temperature and pressure gauge ø 80 mm bottom entry
Case: ABS black

Window: kostil with red pointer

Pressure element: copper alloy Bourdon tube

Temperature element: bimetal spiral spring

Welding: tin alloy for working temperature ranging from -20 +90 °C

Connection: brass - thread 1/4G

Retaining valve: brass - thread 1/4F x 1/2M supplied together

Amplifying movement: brass for precision clockwork

Accuracy: Cl. 1,6

Protection: IP 31

TIRP/TIRF - 80

Codice/Part. No	Denominazione/Description	Esecuzione standard/Supplied standard	Conf./Pack.
TI80003PR	TIRP-80 0-2,5 bar 0/120°C VR1/2		50
TI80004PR	TIRP-80 0-4 bar 0/120°C VR1/2		50
TI80006PR	TIRP-80 0-6 bar 0/120°C VR 1/2		50
TI80003FR	TIRF-80 0-2,5 bar 0/120°C VR1/2+AC	AC=Anello cromato/Chromed ring	50
TI80004FR	TIRF-80 0-4 bar 0/120°C VR1/2+AC	AC=Anello cromato/Chromed ring	50
TI80006FR	TIRF-80 0-6 bar 0/120°C VR1/2+AC	AC=Anello cromato/Chromed ring	50

VR: Valvola di ritegno 1/4F x 1/2 M fornita standard
Retaining valve 1/4F x 1/2M supplied standard

Su richiesta esecuzioni diverse e personalizzate
On request only we are available for special and personalized versions